

## DECK PROOF

*100% ACRYLIC, DECORATIVE, ELASTOMERIC WATERPROOF COATING*



### **DESCRIPTION:**

DECK-PROOF is an acrylic based, decorative weatherproof coating for all masonry surfaces. Our new elastomeric polymers are designed for high-performance demands of masonry, concrete block, brick, stucco and Fibre/cement boards. Décor-Proofer provides excellent tint retention and durability over masonry surfaces. With superior alkali and efflorescence resistance, our coating will assure longer coating life and lower maintenance costs. It prevents entry of water in walls and also prevents growth of fungi, algae, mildew etc.

### **ADVANTAGES:**

- ✓ Single component, ready to use coating
- ✓ Can be applied on damp surfaces
- ✓ Can withstand expansion, contraction or deformation
- ✓ Vapour permeable, hence breathable temperature resistance upto 110°C
- ✓ Excellent adhesion to almost all types of surfaces
- ✓ Weatherproof and Waterproof

### **AREAS OF APPLICATION:**

DECK-PROOF is recommended on external surfaces for decorative, waterproof and weatherproof purposes. It can be used on all kinds of masonry surfaces, concrete blocks, bricks etc

**SPECIFICATIONS:**

Base	Acrylic
Colour	Available in Various Shades
Appearance	Semi-Viscous Liquid
System	Single Component
Finish	Smooth & Matt
Drying Time:	
Surface Dry	2-3 Hours
Hard Dry	8-10 Hours
Recommended Coats	2
Coverage	70-75 sq.ft./litre/coat on smooth surface
Dry Film Thickness	65 microns/coat
Resistance to Heat	Upto 80° C.
Cold Resistance	Upto 5° C
Scratch Hardness	Excellent
Flash Point	Above 30° C.

**PREPARATION:**

Life of DECK-PROOF is directly dependent on the surface preparation and quality of cleaning. Wire brush the surface from loose dirt, dust, flaking paints mortar dropping etc. Remove all algae fungal growth wash with clean water. For new surfaces apply one primer coat of Primer-W30. Fill visible cracks with **CRACK-FIX** Caulking Compound. There after apply minimum two coats of **DECK-PROOF** at an interval of 6-8 hours between each coat.

**METHOD OF APPLICATION:**

Stir the contents in the container well with a mechanical stirrer or wooden stick. The product does not need any addition of water and is ready to use. Therefore, apply by brush, roller or spray and let it dry for 4-6 Hours. Apply second coat and let it cure. During application, protect coating from dust, dirt and water.

**CLEANING OF TOOLS :**

Wash all containers, brushes, tools and hands with water.

**SAFETY PRECUATIONS:**

Keep away from naked flames/lights. Do not smoke near application area. Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

**PACKING:**

Available in 4 & 20 Litres.

**WARRANTY CLAUSE:** *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*