



ACECOATS[®]
the complete construction solution

A  **ASSOCIATED**[®]
CHEMICALS BRAND

A-103, Gurudev Apartment, R.C. Marg, Opp Telephone Exchange, Chembur Naka, Chembur, Mumbai - 400 071
TEL: 022-65752002 / 2378 / 25277937 / 43 FAX: 022-25277841
E-MAIL: assochem@mtnl.net.in; associatedchemicals@hotmail.com WEB: www.associatedchemical.com

CONSTRUCTION CHEMICALS READY RECKONER

WATERPROOFING SOLUTIONS			
S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	TRANSPROOF	TRANSPROOF is a transparent waterproof chemical + primer. It is a single component transparent coating, which seals concrete and other absorbent surfaces. It is primarily used as a bonding agent for Blanc Water Proofer . It can also be used as a primer/bonding agent for other waterproofing products.	WHITE BLACK TERRACOTTA BRICK RED
2	BLANC WATER PROOFER	BLANC WATER PROOFER is a ready to use, 100% acrylic water proof chemical which creates a strong and scratch resistant film, fully seals hairline cracks and acts as an effective barrier against moisture, water and atmospheric impurities. It is primarily used for terrace waterproofing. It is also used on parapet walls, outer and inner walls, basements, as an overcoat on AC sheets, GI sheets and insulated roofs.	WHITE GREY TERRACOTTA
3	BLANC WATER PROOFER-HB-400	BLANC WATER PROOFER-HB-400 is a high build, pure acrylic, elastomeric waterproof chemical coat. It is for waterproofing of old and new build up roofs. It is UV resistant had much better abrasion resistance than any standard waterproofing of terraces. It is also used on parapet walls, outer and inner walls. Basements, as an overcoat on AC sheets, GI sheets and PUF insulated roofs.	WHITE GREY TERRACOTTA
4	ACRYPRIME-20	ACRYPRIME-20 is primarily used as a bonding agent for Blanc Water Proofer-HB-400 . It can also be used as a primer/bonding agent for other waterproof chemicals.	WHITE / BLACK / TERRACOTTA BRICK RED
5	BITUSEALER	BITUSEALER is a cold applied bituminous bonding coat which is to bond bitumen based waterproof coatings. It is designed such that it seals porous surfaces and encourages the adhesion of bituminous waterproof coatings.	BLACK
6	BITUCOAT	BITUCOAT is a cost effective and short-term waterproofing system for various types of treated/untreated surfaces. It is an ideal economic solution for preventing quick and easy repairs for waterproofing of flat concrete roofs, pitched roofs, AC/GI sheet roofs, gutters, iron, steel, masonry or concrete surfaces.	BLACK
7	BITUCOAT-PLUS	BITUCOAT-PLUS is a rubberized water proof coating, based on synthetic rubber and organic chemicals. It is a single component, ready to use black coating which can be applied to dry or damp surfaces. BITUCOAT-PLUS can be used for waterproof of terraces, parapet walls, AC/GI sheets, gutters, roofs of buses, car chesis etc. and is extremely useful for coating for inside and outside water tanks.	BLACK

8	AQUASEAL-PMBM	AQUASEAL-PMBM is a polymer modified bituminous waterproofing membrane. It is used as waterproofing membrane for concrete deck and bridges. The membrane protects the concrete structure from the corrosive effects of deicing salts. It is also used for basement, waterproofing for stopping capillary action, waterproofing application for reservoirs, tunnels, car parking.	BLACK
9	TERRACOAT	TERRACOAT is a white colour, single component, pure acrylic waterproof coating. It is primarily used as a waterproof coating on terraces. It is also used on parapet walls, outer and inner walls, basements, as an overcoat on AC sheets, GI sheets and PUF insulated roofs.	WHITE
10	ISOGUARD-WP	ISOGUARD-WP is a pure acrylic polymer based liquid specially designed for making polymer modified cementitious based waterproof coatings. It is the most cost effective polymeric waterproofing solution. ISOGUARD-WP is mainly recommended for waterproofing of terraces, toilets, bathrooms, sunken slabs, basements and also water tanks. It can be used on floor or external walls. It can be used on sunken portion of bathrooms, toilets, balconies etc.	GREY CEMENTITIOUS FINISH
11	MEGACRETE-ACR	MEGACRETE-ACR is an acrylic polymer based liquid specially developed for making polymer modified cementitious based coatings for water proofing systems and repair. It is also suggested for use as bonding coat with old to new concrete, and plaster and for repairing of plaster and concrete.	GREY CEMENTITIOUS FINISH
12	MEGACRETE-SBR	MEGACRETE-SBR is primarily used for spalled concrete structures such as beams, columns, chajjas, parapets etc. it is also used for waterproofing of terraces, sunken, slabs, chajjas, parapets, etc. furthermore, it is used as a bonding agent for tiles, panels, bricks, stones etc.	GREY CEMENTITIOUS FINISH
13	POLYGUARD-IWC	POLYGUARD-IWC is a two component, polymer modified, heavy duty flexible coating. POLYGUARD-IWC is usually recommended for tanks in fisheries, portable water containers, reservoirs, ponds, swimming pools, silos, sumps, foundation protection, reinstatement of tie-bar holes, protection against brackish water and all water and chemical storage tanks.	GREY CEMENTITIOUS FINISH
14	POLYPROOF-2K	POLYPROOF-2K is a two component, polymer modified cementitious coating with high adhesion to both steel and concrete. POLYPROOF-2K can be applied on all kind of roofs, portable water tanks bathroom sunken slabs, kitchens etc. it is also applied on basements, retaining walls, structural surfaces of cellars, concrete roofs, slabs, floors, balcony floor slabs, water tanks and swimming pools. Furthermore it can be applied on bridge decks, canals and dam wall, structural surfaces of dykes, waterproof coating (bottom coat) for marble, granite and other natural stones.	GREY CEMENTITIOUS FINISH
15	POLYPROOF-2KC	POLYPROOF-2KC is a acrylic based chemicals. It is used to waterproof, bathrooms, sunken slabs, kitchens, basements, concrete roofs, slabs, floors,	GREY CEMENTITIOUS FINISH
16	MASTERCOAT	MASTERCOAT is white colour; single component, anti-fungal, water based, pure acrylic and micro fibre based waterproof coating. It creates an ultra-strong and scratch resistant film and seals hairline cracks. It is a three coat, high build system that acts as a negative barrier against moisture, water and other atmospheric impurities. MASTERCOAT is primarily used as a waterproof coating on terraces. It can be also used on parapet walls, outer and inner walls, basements, as an overcoat on AC Sheets, GI Sheets and PUF insulated roofs.	WHITE / GREY

ACECOATS EXCLUSIVE

S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	PRIMER-W30	PRIMER W-30 is single component, specially formulated primer which acts as a primer as well as a binder over plastered and painted surfaces. PRIMER -W30 can be applied to surfaces such as parapets, chajjas, and external wall of buildings etc. and as primer coat for ENDODAMP-414 and other paints, distempers. Also, it is applied over lime plasters and as primer before cement based paints.	WHITE
2	DECOR PROOFER	DECOR PROOFER is a waterborne acrylic elastomeric polymer for masonry coatings with outstanding tint retention and excellent durability over masonry substrates. DECOR-PROOFER is recommended on external surfaces for decorative, waterproof and weatherproof purposes. It can be used on all kinds of masonry surfaces, concrete blocks, bricks etc.	VARIOUS SHADES
3	NODROPS-ACC	NODROPS-ACC is an anti-condensation coating. It Inhibits Condensation by Absorbing Moisture and Improving Insulation.	WHITE
4	HYDROPOXY-919	HYDROPOXY-919 is a two component, water based, epoxy coating that prevents rising dampness, efflorescence and withstands negative hydrostatic pressure. HYDROPOXY-919 is used to interior damp proofing from external walls. It is used on walls where acute dampness persists. Also it can be applied to sunken slabs, basements, lift pits, water tanks, and swimming pools as a damp proofing coating in preconstruction stage.	WHITE
5	HIGHGLOSS-XL	HIGHGLOSS-XL is a two component, epoxy based, colourless liquid coating. HIGHGLOSS-XL can be used over a variety of surfaces like wood, concrete, metal, stone, all kinds of household articles, furniture, wooden floorings, bathroom doors, stone artifacts, metal objects, ceramic tiles etc. it can also be used on industrial flooring over epoxy treatment as a finish coat to provide high gloss and a hygienic look.	CLEAR GLOSSY COAT
6	SO COOL-500	SOCOOL-500 is a heat reflective coating. It can be applied on all masonry surfaces like external wall of buildings, roots parapets etc. it can also be applied on industrial roofs of GI, AC sheets etc.	WHITE
7	SYLCOSEAL	SYLCOSEAL is a solvent based, colourless, low viscosity penetrating type sealer coating. Ideally suited for all types of external surfaces and has a very wide range of applications. It is ideal for all types of buildings including heritage buildings, external facades be brick, plaster, concrete, pebble plaster, stone, marble, precast block or slabs and other porous building materials.	CLEAR COAT
8	ENDODAMP-414	ENDODAMP-414 is a 100% acrylic, anti-dampness coating. It is a single component, ready to use coating which acts as a barrier to moistures and water. It can be used for interior and exterior applications.	WHITE
9	DECKPROOF	DECK-PROOF is an acrylic based, decorative weatherproof coating for all masonry surfaces. DECK-PROOF is recommended on external surfaces for decorative, waterproof and weatherproof purposes. It can be used on all kinds of masonry surfaces, concrete blocks, bricks etc.	VARIOUS SHADES
10	APROCOOL-500	APROCOOL-500 has been specially formulated to reflect heat and thus save energy costs. APROCOOL-500 can be applied on all masonry surfaces like external walls of buildings, roofs, parapets etc. it can also be applied on industrial roofs of GI, AC Sheets etc.	WHITE
11	BLANC WATER PROOFER-PLUS	BLANC WATER PROOFER-PLUS is a white colour, single component, pure acrylic waterproof coating plus heat reflective coating. BLANC WATER PROOFER-PLUS is primarily used as a waterproof + heat reflective coating on terraces. It is also used on parapet walls, outer and inner walls, basements, as an overcoat on AC Sheets, GI Sheets and PUF insulated roofs.	WHITE / GREY / TERRACDATA
12	SPORTS COAT	SPORTS COAT is a flexible, hard wearing, 100% acrylic Tennis and basket ball Court coating, with good resistance to water in both acid and alkaline conditions.	VARIOUS SHADES

ANTI-CORROSIVE COATINGS

S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	EP-ZINC-PRIMER	EP-ZINC-PRIMER is a two component, zinc rich epoxy primer, which imparts cathodic protection to base metal and also prevents creeping corrosion under film. It can be used on crest gates, floating roofs or tanks, structural steel in docks, refineries, building and other industries, structural equipments like cranes etc. of chemical handling units, bridges and jetties.	GREY
2	EP-GI-PRIMER	EP-GI-PRIMER is a two comment epoxy primer, specially formulated to give improved bonding on galvanized iron surfaces and aluminium.	SILVER GREY
3	EP-ZINCHROM-PRIMER	EPOXY ZINCHROM PRIMER is a two-component, ZINC CHROMATE EPOXY PRIMER containing zinc chromate pigment. It has excellent adhesion to steel and galvanized surfaces.	YELLOW
4	EP-REDOX-415	EP-REDOX-415 is a two-component, red oxide epoxy primer. EP-REDOX-415 has excellent adhesion to steel and other metal surfaces.	RED
5	CRP-70	CRP-70 is flexible, hard wearing chlorinated rubber paint, with good resistance to water in both acid and alkaline conditions. CRP-70 is particularly suitable in conditions where conventional paints may fail. It is used in dairy parlors, silage Pits and Sewage Installations. It can also be used as a Swimming pool Paints on properly treated surfaces.	VARIOUS SHADES
6	TARPOXY-222	TARPOXY-222 is a coal tar epoxy, which is used as a protective corrosion inhibitor coating material in hydraulic steel construction such as inhibitor coating for sluices, harbour installations, steel sheet piling, bridges, bridge decks etc. Furthermore, TARPOXY-222 can be used as an anti-corrosive coating material for concrete, plaster, iron and steel, especially suitable for sewage works. For e.g. coating sewage pipes, sewage treatment plants, decomposition silos etc.	BLACK
7	GLOSSEPOX-777	GLOSSEPOX-777 is a two component, high gloss epoxy enamel paint coating. This is usually applied after any of the epoxy anti-corrosive primers as a top coat. GLOSSPOX-777 is used as a protective coating where high chemical resistance is required, e.g. internal lining of storage tanks, urea prill towers, structural steel machinery and equipment, conveyor system, pipelines; especially in fertilizer plants, chemical plants, petrochemical complexes, pharmaceuticals, dairies, offshore structures, abattoirs & electronic industries.	VARIOUS SHADES
8	CONRUST	CONRUST is a unique water white chemical liquid coating which when applied to a rusty metal surfaces, reacts with the rust and converts the same into a phosphate coating, thus making the surface paintable.	CLEAR
9	OXYCOAT	OXYCOAT is a speciality product, which has anti-corrosive properties to guard all kinds of surfaces and substrates. It is conventionally used to shielding the internal surfaces of tanks, steel pipes, sewage lines/drainage lines etc.	BLACK

INDUSTRIAL GROUTS & REPAIR

S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	EP INJECTION GROUT	EP INJECTION GROUT is a solvent free crack injection material. It helps bonding of concrete cracks permanently. It is also used in repair of crack concrete areas in floors, walls, tanks & sea walls. It can be easily injected into cracks & honey combing in concrete & masonry.	N.A.
2	EPSIN-3G	EPSIN-3G is a three component, epoxy resin, free flowing grout. It is used for high strength grouting and fixing of anchors, crash barrier posts, fence and railing posts, machine bases, vibrating machines, pumps and presses, bridge bearings, mechanical joints like roads and bridges, light rail and permanent way in tunnels, over bridges, starter bars and tie rods.	OFF WHITE
3	MICROCON-1000	MICROCON-1000 is a one component, free flowing micro concrete, suitable for repairs to all kinds of concrete structures.	N.A.
4	CEMAGROUT	CEMAGROUT is general purpose, non-shrink, cementitious grout. Ready to use grout when added with controlled quantity of water, can achieve a free flowing or a paste type of consistency for various uses in the construction industry. These include bedding in precast unit in walls roofs, slabs, anchor bolts, machinery foundation, turbines, generators, filling holes of scaffolding supports, framework ties etc.	N.A.
5	REPID REPAIR X	REPID REPAIR X is an acrylic rapid repair mortar available in single and two components. It can be used in filling concrete floors in various factories having heavy traffic, loading decks, good for cold storages without shutting down, quick and strong repairs to staircase of concrete, marbles or granite, Expressways, highways, ramps, driveways, bridge decks, aprons, and runways, large tanks, reservoirs, sumps, aqueducts etc.	N.A.
6	TILE GROUT	TILE GROUT is a single component product, containing polymers, UV resistant properties and special additives. It has excellent adhesion properties and is used to fill gaps between tiles, mosaics, marble and natural stones.	VARIOUS SHADES
7	TOPFIX-2K	TOPFIX-2K , is a three component, high build repair material, mainly for repair work of concrete, bitumen or any other horizontal surface. It is used where rapid setting and minimum traffic interruption is required. It is most suitable for repairs of concrete, kota, trimix and bitumen surfaces in roads, airfields and factories.	GREY
8	ACEBLOCK-GRP	Block fixing adhesive based on a blend of special by chemicals	GREY COLOUR SEMI LIQUID / PASTE

FLOORING SOLUTIONS

S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	EPOXYBOND-600	EPOXYBOND-600 is a specially developed flooring compound and is used as a primer for the application of epoxy systems. It is Excellent Bonding Agent/Adhesion Promoter.	CLEAR
2	FLOROPOXY-701	FLOROPOXY-701 is a two component epoxy resin based floor coating. It is meant for surfaces where there is light traffic. It is used in places where dust-free and hygienic conditions are required. It is recommended for pharmaceutical and electronic factories, operation theatres, dairies etc. where hygiene is a key factor. Also it can be applied in pre-fabricated homes, containers, tank farms, finishes etc.	VARIOUS SHADES
3	FLOROPOXY-801	FLOROPOXY-801 can be used on concrete surfaces where heavy traffic exists. It is used in places where dust-free and hygienic conditions are required. It is recommended for pharmaceutical and electronic factories, operation theatres, dairies etc. where hygiene is a key factor. Also it can be applied in pre-fabricated homes, containers, tank farms, fisheries, sports centres, spas, food and drink industries, warehouses etc.	VARIOUS SHADES
4	FLOROPOXY-SL-PLUS	FLOROPOXY-SL-PLUS is a self-leveling, heavy duty, epoxy based flooring compound. FLOROPOXY-SL-PLUS can be used where there is high abrasion resistance, chemical resistance, and dust free and hygienic conditions required. It is usually recommended for use in garages, showrooms, exhibition halls, operation theatres, hospitals, food and pharmaceutical industries, factories, engineering units, fertilizer plants, warehouses, workshops, sports centres, aircraft hangars etc.	VARIOUS SHADES
5	INSTA-ESM	INSTA-ESM is an instant water proof cementations anti-skid coating, which when applied stops leakage, dampness, rising dampness, seepage of water from internal or external masonry walls, R.C.C. Slabs., tanks, basements, swimming pools, parking lots, silos, sumps etc.	CEMENT GREY
6	EPM-SL-90/EPM-TL-93	EPM-SL-90/EPM-TL-93 are epoxy mortars available in different grades, mainly being self-levelling and trowel grade respectively. The self-levelling mortar is usually used for floor topping, cavity fillings, beddings etc., whereas the trowel grade is used for vertical surfaces. It is used in vertical column repairing, honeycomb problems in RCC, foundations of heavy vibrating machinery, fixing bearings, repair of cavities, fixing of acid proof tiles in chemicals plants, any concrete structure repair such as tanks, pipes, roads, airport runways etc.	CEMENT GREY
7	SPARKLEAN	SPARKLEAN is a specially formulated chemical cleaner for cleaning of greasy, oily surfaces. The use of acids is normally not recommended in factories where immediate rusting occurs. This chemicals cleaner is based on complex solvents and can be safely used in factory environments. Normally, it is used in cleaning oily floors or any surface which needs to be oil free.	CLEAR
8	POLYKOTE-WB	POLYKOTE-WB is a complex blend based on urethane polymers which produces systems with outstanding abrasion, impact and chemical resistance coupled with high degree of flexibility. It is used in industrial flooring, Dairy and Hotel Industry, car park decking, warehouse Floors, non-slip ramp ways, Bridge Decks, Pedestrian walkways, Residential garages, Food Processing Plants, Helipads and Trafficable Roof.	VARIOUS SHADES

POLYURETHANE COATINGS

<u>S.NO.</u>	<u>PRODUCT NAME</u>	<u>DESCRIPTION / APPLICATION</u>	<u>FINISH AFTER APPLICATION</u>
1	CRYSTAL COAT-300	CRYSTALCOAT-300 is a single component polyurethane waterproof coating specially formulated for tanks, swimming pools, podiums, etc.	CLEAR
2	PU-501	PU-501 is a two component, polyurethane coating, ideally suited for new and maintenance work and for substrates like concrete, cementitious surfaces, asbestos, GI sheets, MS and all metals.	VARIOUS SHADES
3	PU-DECOR	PU-DECOR is a decorative + protective (Anti-Bacterial) coating for almost all surfaces. It is ideally suited for hygienic conditions such as pharmaceutical industrial, hospitals, hotel kitchens, health clubs, spas and food industry. It is used on horizontal + vertical surfaces. Due to its smooth and satin finish, it can be used in bath tubs, ceramic tiles in bathrooms to give them a new look.	VARIOUS SHADES

JOINT SEALANTS

<u>S.NO.</u>	<u>PRODUCT NAME</u>	<u>DESCRIPTION / APPLICATION</u>	<u>FINISH AFTER APPLICATION</u>
1	FIX 'N' BOND	FIX 'N' BOND is a high-quality, plasto-elastic one-component joint acrylic sealant. FIX 'N' BOND is used to fill cracks in masonry, concrete, terraces, concrete precast blocks, slabs, brick linings. It is used to fill gaps between various structures such as aluminium sliding windows, wooden frames, door, baseboards etc. it is used to fill joints of GI/Cement pipes, AC/GI sheets, gutters, flashings etc.	WHITE
2	BITUFULL	BITUFULL is a Rubberized joint filler Compound used to fill crack fractures in asphalt surfaces, thus avoiding future maintenance resulting from exposed and untreated cracks. BITUFILL is used to fill cracks of CI/cement drainage pipes, AC/GI sheets, gutters, joints, cracks of upto 5mm. in masonry surfaces, terraces, basements, concrete precast blocks, slabs, brick linings, water tanks, irrigation canals etc.	BLACK
3	KRACK 'O' FILL	KRACK 'O' FILL is polymer modified power material, meant for filling cracks in plastered surface. KRACK 'O' FILL can be used to fill cracks sizes in horizontal or vertical areas of buildings & structures. Also it is used to level the undulation of the unplastered or plastered ceilings and walls before painting. It is used to provide smooth finish to brick, stone, and wood works.	WHITE

4	POLYSEAL-201	POLYSEAL-201 is a two part polysulphide based joint sealant based on a high grade of synthetic rubber, having outstanding resistance to U.V. light, chemical attack, industrial/atmospheric pollution etc. POLYSEAL-201 is used in expansion joints in reinforced concrete structures such as bridges, expressways, reservoirs, runways, basements, subways and water retaining structures.	BLACK
5	POLYSEAL-MAX	POLYSEAL-MAX a two component acrylic polymer modified sealant with excellent adhesion. It is ideal for all types of joints in precast blocks, slabs, paving blocks etc. Also it is used in joints in building construction, airports, highways, concrete rain pipes, sewers and cracks in RCC structures.	BLACK / CEMENT GREY
6	TILE 'O' BOND	TILE 'O' BOND is a specially formulated dry powdered glue, for fixing of tiles. It is used to bound ceramic, glazed tiles, mosaic, marble, granite and stone tiles to concrete surfaces, for walls and floors, and for laying new tiles on old tiling.	GREY
7	CRACK-FIX	CRACK-FIX is a high quality, plasto-elastic, one component and acrylic sealant. It is an ideal, general purpose construction sealant. CRACK-FIX is used to fill cracks in masonry, concrete, terraces, concrete precast blocks, slabs, brick linings. It is used to fill gaps between various structures such as aluminium sliding windows, wooden frames, door, baseboards etc. it is used to fill joints of GI/Cement pipes, AC/GI sheets, gutters, flashings etc.	WHITE
8	ACROSEAL	ACROSEAL sealant is a solvent based sealant, which is a blend of acrylic and rubber. It is best suited for cracks and joints, indoor and outdoor, which require certain amount of elasticity.	WHITE

ADMIXTURE

S.NO.	PRODUCT NAME	DESCRIPTION / APPLICATION	FINISH AFTER APPLICATION
1	CONCURE	CONCURE is already to use formulation that provides the complete development of concrete's wear resistance and strength properties while accelerating curing time. CONCURE is used in curing of concrete in irrigation canals, highways, runways, roofs, cooling towers, pre-cast pipes, slabs, blocks and sloping structures.	N.A.
2	CORIN-315	CORIN-315 is a liquid corrosion inhibiting admixture for steel reinforced concrete which provides dual level of corrosion protection to steel.	N.A.
3	EPCRETE	EPCRETE is a unique state of art, two component, water soluble epoxy additive for use in mortars and concrete requiring high degree of strengths and impermeability.	CEMENT GREY
4	FINECRETE	FINECRETE is an integral waterproofing admixture of concrete, which converts water soluble compounds present in concrete, into insoluble silicates, it possesses good plasticizing properties, avoids segregation and provides cohesive mix.	N.A.
5	FINEMIX-FRX	FINEMIX-FRX is a high range plasticizer cum retarder. It is ideal for onsite batching plants.	N.A.
6	ACEFLOW-FRX	ACEFLOW-FRX is a high range plasticizer cum retarder for improver workability concrete for onsite batching plants.	N.A.
7	ACEFLOW-CRX / MRX	ACEFLOW-CRX is a strong plasticizer cum retarder. It is ideal for onsite batching plants for achieving high strength.	N.A.
8	ACEFLOW-RAS	ACEFLOW-RAS is a medium range plasticizer cum retarder for low to medium grade concrete.	N.A.
9	ACEFLOW-ARP	ACEFLOW-ARP is a medium range plasticizer cum retarder for low to medium grade concrete.	N.A.
10	FINEMIX-FRX-PLUS	FINEMIX-FRX-PLUS is a high range super plasticizer cum retarder for improving concrete workability & strength. It helps in reducing water content without affecting concrete strength.	N.A.

11	ACEFLOW-FRX-PLUS	ACEFLOW-FRX-PLUS is a high range superior plasticizer for long duration workability & high strength of concrete. It reduces the usage of water without affecting concrete strength.	N.A.
12	ACEFLOW-RAS-PLUS	ACEFLOW-RAS-PLUS is a superior super plasticizer for long duration workability & high strength.	N.A.
13	TACKPLAST	TACKPLAST is a specially formulated bonding agent for plasters which, when added in the recommended dosage in cement, increases the bonding strength between plaster and old concrete.	N.A.
14	ULTRAFLOW LW PCE	A PCE based plasticizer for excellent dispersion & slump retention for concrete upto M-45.	N.A.
15	ULTRAFLOW MID PCE	A PCE based super plasticizer for high strength & slump retention. It is used to increase concrete strength & durability.	N.A.
16	ULTRAFLOW HPCE	A PCE based super plasticizer cum water reducer for concrete strength ABOVE M-60 – it is a hyper plasticizer for high strength concrete & slup retention.	N.A.